C6T BLACK 2022 HYBRID SERIES

HY SPEED IN CO.

For the first time, C6™ hybrid and iron shafts have been broken out into individual parts to allow for ease of fitting. The new C6 Hybrid and Iron shafts feature a striking updated black cosmetic and provide a smooth release and wide versatility in a mid-launch, mid-spin profile.

C6™ BLACK Iron and Hybrid shafts are available in a stunning new cosmetic and feature a unique profile designed to deliver smooth feel and consistency swing-to-swing.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip (in)	Butt OD(in)	Torque (deg)	Kick Pt.
C6™ BLACK Hybrid 40	R3	42	49	0.370	5.5	0.586	5.1	Mid
C6™ BLACK Hybrid 50	R3	42	56	0.370	5.5	0.602	4.7	Mid
C6™ BLACK Hybrid 60	R2	42	67	0.370	5.5	0.592	4.2	Mid
C6™ BLACK Hybrid 60	R	42	69	0.370	5.5	0.594	4.2	Mid
C6™ BLACK Hybrid 70	R	42	78	0.370	5.5	0.601	4.0	Mid
C6™ BLACK Hybrid 80	S	42	84	0.370	5.5	0.608	3.9	Mid

FITTING GUIDE

Driver Speed MPH/YDS	80/210	81-90/210-239	91-105/240-259	106/260
C6™ BLACK 40	R3			
C6™ BLACK 50	R3			
C6™ BLACK 60	R2	R		
C6™ BLACK 70		R		
C6™ BLACK 80			S	

INSTALLATION | TIP TRIMMING INSTRUCTIONS

1i/1h	2i/2h	3i/3h	4i/4h	5i/5h	
0"	0"	0.5"	0.75"	1.0"	

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our dealer locater.